

Interactive Display

NEC MultiSync CB861Q



- Samarbejde ud af boksen – takket være indlejret computer med indbyggede notatværktøjer og trådløse præsentationsfunktioner.
- Beskyttelsesglas – hærdet højkvalitetsglas beskytter panelet, men samtidig giver det en perfekt touch-oplevelse med blændfri belægning for at minimere genspejling og fingeraftryk.
- Omkostningsbesparende enhedshåndtering – nemmere, centraliseret styring af alle forbundne NEC-enheder ved hjælp af NaViSet Administrator 2 softwareværktøjet.
- Multi-Touch – ægte multi-touch understøtning med op til 20 samtidige touch-punkter.
- Enkel betjening – med nem adgang foran til USB-porte og betjeningslementer for de vigtigste funktioner.

Specifikationer

DISPLAY MODULE DATA

Panel Technology	IPS with Direct LED backlights
Native Resolution (Pixels)	3840 x 2160
Diagonal Size (inches / cm)	86 / 217.4
Aspect Ratio	16:9
Backlight Technology	LED
Brightness (cd/m2)	350
Contrast Ratio	1200:1
Response Time (grey to grey avg) ms	8
Viewing Angle (H/V) 0 CR >10	178 horizontal / 178 vertical (typ. at contrast ratio 10:1)

TOUCH INTERFACE SPECIFICATION

Technology	Infrared Touch
Number of Touch Points	20
Coating / Filter	Anti-glare
Screen Hardness (H)	7
Operating System Compatibility	Native Multi-Touch: Windows 7, Windows 8, Windows 10, Linux, Android; Default Mouse: Windows XP, Windows Vista, Mac OS X
Light Transmission [%]	88 (+ / - 1 %)
Reflection Rate [%]	4
Touch Method	Finger; Gloves; Stylus (≥ 8 mm)
Data Interface	USB-HID
Palm Rejection	No
Windows Ink	No

WEIGHTS AND MEASURES

Bezel Size (L/R) mm	17.7
Bezel Size (U/L) mm	17.7 / 45.7
Product Dimensions (W/H/D) mm	1,957.1 x 1,159.8 x 86.8
Product Weight Without Stand (Kg)	67.3

CONNECTIVITY (AUDIO/VIDEO) INPUT

HDMI	3
VGA	1
Audio 3.5mm Jack	1

CONNECTIVITY (CONTROL/SERIAL DATA)

RS232C IN	1
LAN Port	2
USB	8

KEY SPECIFICATIONS

Special Characteristics	AMX NetLinX Support; HDMI with UHD at 60 Hz; NaViSet Administrator 2; Scheduler
Operating Time	12 / 7
Built in Speakers (W)	2 x 12 W
Cabinet Colour	Black

POWER SUPPLY AND OPERATING ENVIRONMENT

Power Consumption (W) (Operating MAX)	620
Operating Temperature (oC)	+0 to +40
Humidity (%)	10-90

INSTALLATION

Landscape	•
Mounting (VESA/Number of Points/Pitch mm)	4; 800 x 600 (FDMI)

CONNECTIVITY (AUDIO/VIDEO) OUTPUT

Audio/Headphone 3.5mm Jack	1
----------------------------	---

ACCESSORIES

Shipping Contents	3 x Stylus; HDMI Cable; Power Cable; Remote Control; USB cable; User Manual; VGA cable; Wall Mount
-------------------	--

