

NEC MultiSync C750Q



- Klar til fremtiden med Open Modular Intelligence Expansion – opgrader dit displays styrke ved at integrere noget NEC-ekstraudstyr til OPS Slot-in PC'er.
- Brugervenlig betjening og drift – smarte installations-, drifts- og vedligeholdelsesfunktioner sikrer præcise præstationer i hele displayets levetid samt besparelser af tid, anstrengelser og ressource
- Omkostningsbesparende enhedshåndtering – nemmere, centraliseret styring af alle forbundne NEC-enheder ved hjælp af NaViSet Administrator 2 softwareværktøjet.
- Missionskritisk, klar til drift 24/7 – valget af industrielle komponenter og omhyggeligt design fokuseret på svære anvendelsesscenarier går hånd i hånd med en imponerende og uafbrudt brugeroplevelse.
- Fremtidssikret signalforbindelse og -bearbejdning – flere native UHD-opløsningsindgange med en genskabelsesfrekvens på 60Hz plus automatisk opskalering til UHD for andre signaler, sikrer "pixelfri vis

Specifikationer

DISPLAY MODULE DATA

Panel Technology	IPS with Edge LED backlights
Native Resolution (Pixels)	3840 x 2160
Diagonal Size (inches / cm)	75 / 189
Brightness (cd/m2)	350, 250 (shipment setting)
Contrast Ratio	1200:1
Response Time (grey to grey avg) ms	8
Viewing Angle (H/V) 0 CR >10	178 horizontal / 178 vertical (typ. at contrast ratio 10:1)
Colour Depth [bn]	1.073 (10bit)
Haze Level [%]	28

POWER SUPPLY AND OPERATING ENVIRONMENT

Power Consumption (W) (Operating MAX)	195 shipping
Operating Temperature (oC)	0 to 40
Humidity (%)	20 to 80

INSTALLATION

Landscape	•
Portrait	•
Mounting (VESA/Number of Points/Pitch mm)	4; 400 x 400 (FDMI); 600 x 400 (FDMI)

CONNECTIVITY (AUDIO/VIDEO) OUTPUT

Audio/Headphone 3.5mm Jack	1
----------------------------	---

ACCESSORIES

Shipping Content	2x AAA batteries; Display; HDMI Cable; Power Cable; Remote Control; Setup Manual
Remote Control Transmitter	Yes
Power Cord	Yes
Mounting Bracket	Optional
Tabletop Stand	Optional

KEY SPECIFICATIONS

Special Characteristics	DICOM Simulation; HDMI ARC; Powered USB Port (10 W); Removable Logo
24/7 Operation Certified	•
Limited Manufacturer's Warranty (yrs.)	3
Local Dimming	•
Built in Speakers (W)	10W + 10W
Cabinet Colour	Black
Temperature Sensor	•
Brightness Sensor	•

WEIGHTS AND MEASURES

Bezel Size (L/R) mm	14.8
Bezel Size (U/L) mm	14.8
Product Dimensions (W/H/D) mm	Without stand: 1,681 x 960 x 71
Shipping Carton Dimensions (W/H/D) mm	1,830 x 1,190 x 280
Product Weight With Stand (Kg)	53
Shipping Weight (Kg)	65.5

CONNECTIVITY (AUDIO/VIDEO) INPUT

HDMI	2
DisplayPort	1
Audio 3.5mm Jack	1

CONNECTIVITY (CONTROL/SERIAL DATA)

RS232C IN	1
LAN Port	1
USB	1

